

Temp. Range		930°C		1200°C (1150°C working)		
Size	Rating	Pyrometer	Digital	Rating	Pyrometer	Digital Temp.
9 x 4 x 4"	1600			2000		
10 x 5 x 5"	2000			2500		
12 x 6 x 6"	3000			3500		
18x 9 x 9"	6000			6500		

OPTIONAL AT EXTRA:-						
A) Blind Temp. Controller with suitable sensor						
B) Electronic Temp. Controller cum indicator						
C) Solid State Fuse						
D) Digital Timer – 999 Minutes						
E) On site Validation					Extra POR	

PLS ASK US FOR MICROPROCESSOR BASED PROGRAMMABLE MUFFLE FURNACE.

SPARE MUFFLE WITH COIL :- Spare muffle wound with heating elements and embedded with heat resistance ceramic fiber wool insulation with extra long terminal for easy wiring.

Temp. Range	Rating	930°C	Rating	1200°C (1150°C working)
9" x 4" x 4"	1600		2000	
10" x 5" x 5"	2000		2500	
12" x 6" x 6"	3000		3500	
18" x 9" x 9"	6000		6500	

Note : Equipment shall be supplied with following documents:-

- Calibration Certificate for controller.
- Material Test Certificate.
- Calibration certificate of Sensor.
- Operation manual of Oven.
- Operational manual of controller.